

Material Safety Data Sheet
PET Products of ZL Engineering Plastics, Inc.



1. Product and Company

ZL Products:

ZL® 1400- Natural
ZL® 1400 - Black
ZL® 1400T - Bearing Grade PET

Manufacture:

Zell-Metall GmbH

Schulstraße 511
A-5710 Kaprun
Tel: +43 6547 8417
Fax: +43 6547 8890
E-mail: zell-metall@zmk.at
Austria/Europe
Website: www.zell-metall.com

ZL Engineering Plastics, Inc.

10908 Strangline Rd
Lenexa, KS 66215
Tel: 913-327-0300
Fax: 913-327-0302
E-mail: info@zlplastics.com
United States/North America
Website: www.zlplastics.com

2. Composition/Information on Ingredients

Stock shapes manufactured of extruded Polyethylenetheraphtalate, known as thermoplastic polyester, possibly stabilizing agents, pigments, fillers, additives.
CAS – number: Not required.

3. Possible Hazards

None.

4. First Aid Measures

Burns caused by molten material require hospital treatment.

5. Fire Fighting Measures

Suitable Extinguishing Agents: Water, water/foam, CO2, ABC extinguisher powder.
Specific Hazards: Treat the material as a solid that can burn. The stock shape or molded parts generally burn slowly with flaming drips. In case of fire appreciable quantities of carbon monoxide are released in combination with irritating and/or toxic substances.
Protection for Fire-Fighters: Do not approach fire in confined space without positive pressure self breathing apparatus and full bunker gear.

6. Measures in case of Accidental Release

Not applicable.

7. Handling and Storage

No special precautions necessary. Unlimited storage possible.

8. Exposure Limits

Components with workplace control parameters: Threshold Limit Value (TLV): a provisional TLV (TWA 8 hours) is advised in accordance with the TLV of nontoxic nuisance dust:
–10 mg/m³ for total dust.
– 5 mg/m³ for respirable dust.
Personal protective equipment: Personal protective gear unnecessary.

9. Physical and Chemical Properties

Appearance

Form: Solid as semi-finished (plate, rod, tube) at 20°C

Color: Natural, grey, or black

Odor: Formaldehyde

Change in Physical State:

Melting point: 225 – 255°C

Ignition temperature: 350°C

Density: 1.36 g/cm³

10. Stability and Reactivity

Thermal Decay: To avoid thermal decomposition, do not overheat.

Avoid temperatures above 350°C

Dangerous by-products of decay: Protect against acid and acid-forming substances.

11. Toxicological Information

In our experience and according to information available to us, the product is not harmful to health provided if it is correctly handled and processed according to the given recommendations.

12. Ecological Information

No indication that this material is being a risk to the environment.

Insoluble non toxic solid material (no water hazard).


13. Disposal Information

Check for possible recycling. Can be dumped with domestic refuse or incinerated in suitable plants in accordance with local regulations.

14. Transport Information

Not classified as hazardous under transport regulation.

15. Rules

 **WARNING:** This product can expose you to chemicals including **Ethlene Glycol** (CAS 107-21-1), which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov.

16. Special Information

The information contained herein is based on the present state of our knowledge and does not therefore guarantee certain properties. Recipients of our product must take responsibility for observing existing laws and regulations.